## SPARK 32 L.E.D. Micro Beacon Lights V23



INPUT VOLTAGE	MAX CURRENT DRAW	
10 – 30V DC	2.0A @ 12V DC	1.0A @ 24V DC

SINGLE COLOUR TYPE (4 CORE)		
BLACK	Connect to Constant Negative Ground	
RED	360 DEGREES Flashing Warning Lights (+) Positive Powered *COLOUR A*	
YELLOW	FLASH PATTERN SELECTION + SYNC-ABLE (+) Positive Momentary	
BLUE	NIGHT MODE Reduce Brightness Intensity (+) Positive Powered	

DUAL COLOUR TYPE (5 CORE)			
BLACK	Connect to Constant Negative Ground		
RED	360 DEGREES Flashing Warning Lights (+) Positive Powered *COLOUR A*		
BROWN	360 DEGREES Flashing Warning Lights (+) Positive Powered *COLOUR B*		
YELLOW	FLASH PATTERN SELECTION + SYNC-ABLE (+) Positive Momentary		
BLUE	NIGHT MODE Reduce Brightness Intensity (+) Positive Powered		

FLASH PATTERN SELECTION	MOMENTARILY Apply POSITIVE Power to YELLOW Wire for		
NEXT PATTERN	PREVIOUS PATTERN	FACTORY RESET	
(>1 SECOND)	(>3 SECONDS)	(>5 SECONDS)	

	FLASH PATTERN LIST				
SINGLE COLOUR		DUAL COLOUR (ALTERNATING)			
P1	FULL - Single Flash @ 125FPM – Group "A"	P1	FULL – Single Flash @ 125FPM		
P2	FULL - Single Flash @ 125FPM – Group "B"	P2	FULL – Double Flash @ 125FPM		
P3	FULL - Double Flash @ 125FPM – Group "A"	P3	FULL – Quad Flash @ 125FPM		
P4	FULL - Double Flash @ 125FPM – Group "B"	P4	ROTATING – Normal Speed – Twin Rotator		
P5	FULL - Quad Flash @ 125FPM – Group "A"	P5	ROTATING – Fast Speed – Twin Rotator		
P6	FULL - Quad Flash @ 125FPM – Group "B"	P6	COMBO – FULL (3) Single + (3) Quad Flash		
P7	ROTATING – Normal Speed – Twin Rotator	P7	COMBO – FULL (3) Double + (3) Quad Flash		
P8	ROTATING – Fast Speed – Twin Rotator	P8	COMBO – (3) Single Flash + (6) Normal Twin Rotator		
P9	COMBO – FULL (3) Single + (3) Quad Flash	P9	COMBO – (3) Single Flash + (6) Fast Twin Rotator		
P10	COMBO – FULL (3) Double + (3) Quad Flash				
P11	COMBO – (3) Single Flash + (6) Normal Twin Rotator	WARNING NOTICE			
P12	COMBO – (3) Quad Flash + (6) Fast Twin Rotator		HIGH INTENSITY WARNING LIGHT		
P13	FULL – Strobe Intensity Flash	DO NOT STARE DIRECTLY INTO LIGHT			
P14	CRUISE – Steady-On @ 50% Brightness				