

KINETIC Series L.E.D. Dash Deck Warning Lights



APPROVALS	CISPR 25 (C3) + SAE J595 (C1) + CE + UKCA ECE R10 + ECE R65 XA1/XA2 XB1
------------------	--

INPUT VOLTAGE	MAX CURRENT DRAW (Single / Twin) Head	
12 – 30V DC	(0.9A / 1.8A) @ 12V DC	(0.4A / 0.9A) @ 24V DC

WIRING HARNESS (4 CORE)	
BLACK	Connect to Constant Negative Ground
RED	COLOUR <u>A</u> Flashing Warning Light Colour (+) Positive Powered
WHITE	COLOUR <u>B</u> Flashing Warning Light Colour (+) Positive Powered
<i>Apply Power to RED + WHITE wires to Activate both WARNING COLOURS</i>	
YELLOW	FLASH PATTERN User Selectable + SYNC-ABLE (+) Positive Momentary
<i>Connect Yellow Wires from Multiple KINETIC Series Lights for Synchronization</i>	

FLASH PATTERN SELECTION		Apply POSITIVE Power to YELLOW Wire for
NEXT PATTERN (<1 SECOND)	PREVIOUS PATTERN (<3 SECONDS)	FACTORY RESET (5 SECONDS)

FLASH PATTERN LIST			
P1	FULL – Fast Single Flash	P11	FULL – Slow Double Flash
P2	FULL – Fast Double Flash	P12	FULL – Triple Flash
P3	FULL – Fast Quad Flash	P13	FULL – Slow Quad Flash
P4	FULL – Fast Octa Flash	P14	FULL – Slow Octa Flash
P5	SPLIT – Fast Single Flash	P15	FULL – Cardinal Flash
P6	SPLIT – Fast Double Flash	P16	FULL – Variable Speed Single Flash
P7	SPLIT – Fast Quad Flash	P17	FULL – Variable Speed Double Flash
P8	SPLIT – Fast Octa Flash	P18	FULL – Emergency SOS Flash
P9	FULL – Slow Single Flash	P19	FULL – Steady On
P10	FULL – Slow Warp Dynamic Variable Flash		

EYESIGHT SAFETY NOTICE

<<< DO NOT STARE DIRECTLY INTO THE LIGHT >>>

BRIGHTNESS & INTENSITY OF LIGHT MAY CAUSE TEMPORARY LOSS OF SIGHT OR PERMANENT EYE INJURY.